

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38		A1	(11) International Publication Number: WO 97/24898
			(43) International Publication Date: 10 July 1997 (10.07.97)
(21) International Application Number: PCT/FI96/00685		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 20 December 1996 (20.12.96)			
(30) Priority Data: 956355 29 December 1995 (29.12.95) FI			
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Upseerinkatu 1, FIN-02600 Espoo (FI).			
(72) Inventor; and (75) Inventor/Applicant (for US only): LAHTINEN, Lauri [FI/FI]; Kurkijointie 7 B, FIN-02140 Espoo (FI).			
(74) Agent: OY KOLSTER AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).			
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: LOAD REDUCTION OF A VISITOR LOCATION REGISTER

(57) Abstract

A problem arises when the data of the visitor location register (VLR) are lost for some reason. In this case, only the visitor location register (VLRn) in whose area the mobile station (MS) is located is known. The mobile station (MS) must then be paged in all location areas (LAn) of the visitor location register (VLR). Such paging of mobile stations causes a significant overload. The overload is reduced, according to the invention, by dividing the area covered by a physical visitor location area (VLR) into areas of a plurality of logical visitor location registers (LVLRn). In connection with location updatings, not only the physical visitor location register (VLR) is stored but also information on the logical visitor location register (LVLRn) in whose area the mobile station (MS) is located; in a problematic situation where the switching centre (MSC) is not aware of the location area of the mobile station (MS), the mobile station (MS) is paged, at least at first, only in the area of the logical visitor location register (LVLRn).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

WO 97/24898

PCT/FI96/00685

1

Load reduction of a visitor location register.

5 The invention relates to mobile communication systems and particularly to reducing the load of their visitor location registers.

10 Figure 1 illustrates the roaming of a mobile station MS in a mobile communication network or in a network subsystem NSS. In this example, the NSS comprises six base transceiver stations BTS1 to BTS6, which can be controlled by one or more base station controllers BSC. Each base station BTS serves one cell. When an MS terminated call is switched through the network NSS, the NSS must know the area in which the MS is to be paged. The area in which the MS is paged is
15 called a location area LA.

The size of the location area LA is a compromise. If the location area is very large, the MS must be paged in the area of several base stations BTS. This means that mobile stations are also paged in base station areas where they are not located. This consumes
20 the capacity of radio channels. If the location area is small, location updatings must be performed frequently. Figure 1 shows, by way of illustration, three location areas LA1-LA3, which cover 1, 2 and 3 base stations, respectively. The base stations BTS continuously broad-
25 cast information on themselves and their environment, such as a base station identifier BSI and a location area identifier LAI. On the basis of the LAI, an MS registered in a BTS knows in which LA it is located at each moment. If the MS, when changing the BTS, observes that the LAI has changed, it sends a location update request or message to the network NSS. The LA of the MS is updated in the visitor location register VLR in whose area the MS is located at that moment. The VLR typically
30 stores e.g. the subscriber's IMSI (International Mobile
35

WO 97/24898

PCT/FI96/00685

2

Subscriber Identity) number, MSISDN number, subscriber service data and LAI.

Information on the VLR in whose area the MS is located is sent to the home location register of the MS. The HLR stores permanent subscriber data, which are not dependent on the subscriber's location at a given moment: e.g. the subscriber's MSISDN and IMSI, subscriber service data, and routing data to the VLR in whose location area the MS is located.

Figure 2 illustrates the setting up of an MS terminated call in a GSM-type mobile communication system. If the MS of Figure 1 is not located within the area of its own home location register, the parts of Figure 2 correspond to those of Figure 1; however, the HLR and VLR are associated with different mobile services switching centres MSC. In step 1, a call arrives at a gateway mobile switching centre GMSC. In step 2, the GMSC defines the subscriber's home location register HLR on the basis of the called subscriber's directory number MSISDN, and sends it a request for routing data. Information on the VLR in whose area the subscriber is located is updated in the subscriber's HLR in connection with location updating. On the basis of this information, the HLR sends the VLR a 'Provide Roaming Number' request in step 3. The IMSI of the MS subscriber is also sent to the VLR in this request. In step 4, the VLR stores the data it has received and assigns a mobile station roaming number MSRN. In step 5, the VLR sends the MSRN it has assigned to the HLR, which in step 6 sends it to the switching centre GMSC that requested the routing data. The roaming number domain is defined in such a way that a call is always directed to the MSC whose VLR has assigned the roaming number in question. On the basis of the MSRN, the GMSC is thus able to route the call forward by sending an

WO 97/24898

PCT/FI96/00685

3

initial address message in step 7 to the MSC indicated by the MSRN.

5 In this example, the MSC finds out on the basis of the MSRN that the call will terminate in its own area. In step 8, the MSC requests the data of the called subscriber from its own VLR call set-up. In a normal case, the VLR returns the requested data in step 9 for setting up the call. This is indicated by arrows 10 and 11.

10 A problem arises when the data of the VLR are lost for some reason. This may happen, for instance, when the VLR is reinitialized, possibly during software updating or equipment maintenance. In this case, only the VLR in whose area the MS is located is known (on the basis of the HLR of the MS). The MS must then be paged
15 in all location areas LA where there are mobile stations whose data are stored in the VLR in question. If the VLR serves a large number of subscribers, such paging of mobile stations causes a significant overload mainly in
20 three areas: 1) between the MSC and the base station system BSS; 2) in the signalling process of the BSS; and 3) on radio channels. The BSS comprises a base station controller BSC and base stations BTS controlled by the BSC. As a result of the overload, some of the MS
25 terminated calls fail.

The object of the invention is thus to provide a method and an apparatus implementing the method in such a manner that the above-mentioned overload problems are solved. The objects of the invention are achieved
30 with methods and systems characterized by what is disclosed in the independent claims. Preferred embodiments are disclosed in the dependent claims.

The invention is based on dividing the area of a physical VLR into areas of a plurality of logical
35 VLRs. When a mobile station performs location updating,

WO 97/24898

PCT/FI96/00685

4

the location update request sent by the VLR to the HLR also contains information on the logical VLR in whose area the mobile station is located. This information is transparent to the HLR, i.e. the HLR stores it but does not react to it in any way.

In the case of an incoming call, signalling takes place as before. In a problematic situation where the VLR is not aware of the location area of the MS, the physical VLR receives the address of the logical VLR of the MS from the HLR with normal signalling. This information is included in a 'Provide Roaming Number' message. The physical VLR thus limits the paging to the area of the logical VLR. In the most extreme case, the area of the logical VLR may even be only one location area.

It is an advantage of the method and system of the invention that the network is considerably less loaded in problematic situations than in prior art systems. Another advantage of the arrangement of the invention is that the modifications to be made in an existing system are relatively small, for instance modifications in the MSC software. The modifications are compatible with the existing systems in every respect. A network can thus employ - simultaneously and in a flexible manner - both switching centres modified according to the invention and switching centres not modified according to the invention.

In the following, the invention will be described in greater detail by means of preferred embodiments with reference to the accompanying drawings, in which

Figure 1 shows the parts of a mobile telephone network that are essential to the invention;

Figure 2 shows the steps of a signalling

WO 97/24898

PCT/FI96/00685

5

process of a mobile telephone network that are essential to the invention; and

Figure 3 shows location areas of a mobile telephone network, divided into areas of a plurality of logical visitor location registers.

With reference to Figure 3, the overload of a mobile telephone network is limited, according to the invention, by dividing the area of a physical visitor location register VLR into areas of a plurality of logical visitor location registers LVLRn. For reasons of clarity, the area of the physical VLR is divided in Figure 3 into areas of only two logical visitor location registers LVLR1 and LVLR2. In practical applications, a suitable number n of LVLRs in the area of one physical VLR could be, for example, 5 to 10. The system of Figure 3 would require the following modifications in the prior art solution of Figures 1 and 2:

1. Defining and naming LVLRs of suitable size. In the naming, it is sufficient to use, for example, 1 or 2 digits after the number of the VLR.

2. The message sent by the MSC to the HLR in connection with the location updating of an MS also contains information on the LVLR in whose area the MS is located. This information is transparent to the HLR, i.e. the HLR processes it as an ordinary number of a physical VLR which is only 1 or 2 digits longer than it would be without the identifier n of the LVLR.

3. In the case of an MS terminated call, the changes will not become visible until the data of the VLR have been lost for one reason or another, i.e. the VLR does not know the location area of the MS. In this case, the MSC (and its VLR) receives the identifier of the LVLR of the MS from the HLR in connection with normal signalling (in a 'Provide Roaming Number'

WO 97/24898

PCT/FI96/00685

6

message). On the basis of this information, the MSC may limit the paging of the MS to only the area of the LVLR.

5 According to the prior art, the following information, for example, is stored in a HLR:

an MS whose IMSI number is	is in the area of a VLR whose GT address is
IMSI	NCC NDC VLRn

10

where:

GT = Global Title

NCC = National Country Code

NDC = National Destination Code

15 VLRn = Visitor Location Register number.

According to the invention, the following information is correspondingly stored in the HLR:

an MS whose IMSI number is	is in the area of a VLR whose GT address is
IMSI	NCC NDC VLRn nn

20

where

25 nn = the number of the LVLR (1 or 2 digits) within the physical VLRn.

The specification of a VLR as LVRLs is implemented according to the invention for instance as software modifications in the MSC. The software modifications are as follows:

30 1. The MSC must keep a log of which location areas LAN belong to which logical visitor location registers LVLRn.

WO 97/24898

PCT/FI96/00685

7

2. In connection with location updating of an MS, the MSC must also send the HLR of the MS information on the LVLRn in whose area the MS is located.

5 3. In problematic situations where the data of the physical VLR have been lost, the MSC must, when paging the MS, at least at first limit the paging to only the LVLRn area where the location of the MS has last been updated.

10 Dividing a visitor location register VLR into (or specifying a VLR as) logical visitor location registers LVLRn reduces the congestion peaks occurring in problematic situations. If the number n of LVLRs within the area of a physical VLR is five, for example, the MS must be paged in an area that is five times
15 smaller, and the load caused by the paging is reduced accordingly. There is, nevertheless, a side effect: the number of location datings grows by the same coefficient. However, the advantages resulting from the reduction of congestion peaks outnumber the drawbacks
20 caused by the additional traffic caused the location datings.

It will be obvious to one skilled in the art that the examples described above are in every respect intended to illustrate the invention, not to restrict
25 it. The invention has been described, by way of example, with reference to a GSM system, but it may also be applied to other kinds of mobile communication systems. The invention and its embodiments are thus not limited to the examples described above, but they may be
30 modified within the scope of the appended claims.

WO 97/24898

PCT/FI96/00685

8

Claims

1. A method for updating location of a mobile station (MS) in a digital mobile telephone network (NSS), wherein a home location register (HLR) stores information on the physical visitor location register (VLR) in whose area the mobile station (MS) is located, characterized in that

- the area covered by a physical visitor location register (VLR) is divided into areas of a plurality of logical visitor location registers (LVLRn); and

- the home location register (HLR) stores, in addition to the physical visitor location register (VLR), information on the logical visitor location register (LVLRn) in whose area the mobile station (MS) is located.

2. A method for paging a mobile station (MS) in the area of a mobile services switching centre (MSC) in a digital mobile telephone network when information on the location area (LA) of the mobile station (MS) has been lost by the switching centre (MSC), characterized in that

- the area covered by the physical visitor location register (VLR) of the switching centre (MSC) is divided into areas of a plurality of logical visitor location registers (LVLRn); and

- the mobile station (MS) is paged, at least at first, only in the area of the logical visitor location register (LVLRn) last indicated by the mobile station.

3. A mobile services switching centre (MSC) in a digital mobile telephone network, said switching centre comprising a physical visitor location register (VLR) and transmitting information to a home location

WO 97/24898

PCT/FI96/00685

9

register (HLR) of the mobile telephone network on the physical visitor location registers (VLR) in whose area different mobile stations (MS) are located, characterized in that

5 - the area covered by the physical visitor location register (VLR) of the switching centre (MSC) is divided into areas of a plurality of logical visitor location registers (LVLRn); and

10 - the switching centre (MSC) also transmits information to the home location register (HLR) on the logical visitor location registers (LVLRn) in whose area different mobile stations (MS) are located.

15 4. A location update message in a digital mobile telephone network (NSS), said message containing information on the visitor location register (VLR) in whose area the mobile station (MS) is located, characterized in that the location update message further contains information on the logical visitor location register (LVLRn) in whose area the mobile
20 station (MS) is located.

WO 97/24898

PCT/FI96/00685

1/2

Fig. 1





Fig. 2




WO 97/24898

PCT/FI96/00685

2/2

Fig. 3



1

INTERNATIONAL SEARCH REPORT

 International application No.
 PCT/FI 96/00685

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04Q 7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0666700 A1 (AT & T CORP.), 9 August 1995 (09.08.95), column 2, line 16 - line 26; column 2, line 41 - column 4, line 15 --	1-4
A	EP 0475865 A2 (NIPPON TELEGRAPH AND TELEPHONE CORPORATION), 18 March 1992 (18.03.92), column 1, line 56 - column 2, line 53 --	1-4
P,A	WO 9607277 A2 (NOKIA TELECOMMUNICATIONS OY), 7 March 1996 (07.03.96), page 3, line 33 - page 6, line 30 -----	1-4

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

- * Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
 - "B" earlier document but published on or after the international filing date
 - "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 - "O" document referring to an oral disclosure, use, exhibition or other means
 - "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

12 June 1997

Date of mailing of the international search report

13.06.1997

 Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

 Christina Halldin
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/06/97

International application No.

PCT/FI 96/00685

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
EP	0666700	A1	09/08/95	CN	1114815 A	10/01/96
				JP	8084364 A	26/03/96
				US	5590398 A	31/12/96
EP	0475865	A2	18/03/92	DE	69125439 D	00/00/00
				JP	4123533 A	23/04/92
				US	5361396 A	01/11/94
WO	9607277	A2	07/03/96	AU	3259095 A	22/03/96
				CN	1135826 A	13/11/96
				EP	0729691 A	04/09/96
				FI	943873 A	24/02/96
				NO	961605 A	17/06/96

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.